VOLUME III: CHAPTER 12

MARINE VESSEL LOADING, BALLASTING, AND TRANSIT

May 1998



Prepared by: TRC Environmental Corporation

Prepared for: Area Sources Committee Emission Inventory Improvement Program

DISCLAIMER

This document was furnished to the U.S. Environmental Protection Agency by TRC Environmental Corporation, Chapel Hill, North Carolina. This report is intended to be a final document and has been reviewed and approved for publication. The opinions, findings, and conclusions expressed are those of the authors and not necessarily those of the U.S. Environmental Protection Agency. Mention of company or product names is not to be considered as an endorsement by the U.S. Environmental Protection Agency or the Emission Inventory Improvement Program.

ACKNOWLEDGEMENT

This document was prepared by TRC Environmental Corporation and revisions made by Eastern Research Group for the Area Sources Committee of the Emission Inventory Improvement Program and for Charles Mann of the Air Pollution Prevention and Control Division, U.S. Environmental Protection Agency. Members of the Area Sources Committee contributing to the preparation of this document are:

Charles Mann, Air Pollution Prevention and Control Division, U.S. Environmental Protection Agency Carolyn Lozo, California Air Resources Board
Kwame Agyei, Puget Sound Air Pollution Control Agency
Kim Cornelison, Louisiana Department of Environmental Quality
Mark Eastburn, Delaware Department of Natural Resources and Environmental Control
Mike Fishburn, Texas Natural Resource Conservation Commission
Charles Masser, Air Pollution Prevention and Control Division, U.S. Environmental Protection Agency
Linda Murchison, California Air Resources Board
Sally Otterson, Washington Department of Ecology
Jack Sipple, Delaware Department of Natural Resources and Environmental Control
Lee Tooly, Emission Factor and Inventory Group, U.S. Environmental Protection Agency
Jim Wilkinson, Maryland Department of the Environment

Other reviewers contributing to this document are:

Allen Ellett, BP Oil Company Rob Ferry, TGB Partnership Tahir Khan, Chemical Emission Management Services

This page is intentionally left blank.

CONTENTS

Section	on		Page
1	Introdu	ection	12.1-1
2	Source	Category Description	12.2-1
	2.1	Category Description	12.2-1
	2.2	Process Description and Emission Sources	12.2-1 12.2-1 12.2-2 12.2-2
	2.3 2.4	Factors Influencing Emissions	12.2-2 12.2-3
3	Overvi	ew of Available Methods	12.3-1
	3.1	Emission Estimation Methodologies	
	3.2	3.2.1 Data Elements	12.3-1 12.3-1 12.3-3 12.3-3 12.3-4 12.3-4
	3.3	Projecting Emissions	12.3-4
4	Preferr	ed Methods for Estimating Emissions	12.4-1
	4.1	Preferred Method	12.4-1
		Inventory Region	12.4-1 12.4-2 12.4-3 12.4-6 12.4-6

CONTENTS (CONTINUED)

Section	on			Page
		4.1.6	Estimation of Emissions from Petroleum Vessels	12.4-9
5	Altern	ative M	ethods for Estimating Emissions	12.5-1
6	Quality	y Assur	ance/Quality Control	12.6-1
	6.1	6.1.1	on Estimate Quality Indicators	12.6-1
7	Data C	Coding F	Procedures	12.7-1
	7.1	Proces	s and Control Codes	12.7-1
8	Refere	nces		12.8-1

TABLES

		Page
12.4-1	Emission Points For Petroleum Vessel Traffic Classifications	12.4-4
12.4-2	Product Type Classifications For Common Petroleum Vessel Commodities	12.4-5
12.4-3	Example Spreadsheet for Sabine-Neches Waterway, TX	12.4-7
12.4-4	Process/ Product Categories	12.4-8
12.4-5	Uncontrolled VOC Emission Factors For Petroleum Carrying Marine Vessels	2.4-10
12.6-1	Preferred Method: DARS Scores	12.6-2
12.7-1	AMS Codes for the Marine Vessel Loading, Ballasting, and Transit Category	12.7-1
12.7-2	AIRS Control Device Codes	12.7-2

EIIP Volume III viii

This page is intentionally left blank.

INTRODUCTION

This chapter describes the procedures and recommended approaches for estimating emissions from marine vessel loading, ballasting, and transit. Section 2 of this chapter contains a general description of marine vessel loading, ballasting, and transit and an overview of available control technologies. Section 3 provides an overview of available emission estimation methods. Section 4 presents the preferred method for estimating emissions from these processes, and Section 5 of this series of documents usually presents alternative emission estimation techniques. For this source category, no alternative methods are known to exist, and Section 5 presents a brief discussion of this issue. Quality assurance issues and emission estimate quality indicators for the methods presented in this chapter are discussed in Section 6. Data coding procedures are discussed in Section 7. Section 8 is the reference section.

This page is intentionally left blank.

12.1-2 EIIP Volume III

Source Category Description

2.1 CATEGORY DESCRIPTION

Petroleum liquids are transported via ships and barges, and on-land transportation. The procedures discussed below relate to marine transport of petroleum liquids. This category does not include emissions from fuel consumed by vessels while in transit or in port. Additional information about petroleum vessels can be found in *AP-42* (EPA, 1996), *AIRS Area and Mobile Source Category Codes* (EPA, 1992), and *Methodologies for Estimating Air Emissions from Three Non-Traditional Source Categories* (EPA, 1993).

2.2 Process Description and Emission Sources

In general, "petroleum liquids" include both crude oil and any refined petroleum product. Refined petroleum products conveyed to fuel marketing terminals and petrochemical industries via ships and barges include gasoline, kerosene, distillate oil, residual oil, jet fuel, and other petroleum-derived chemicals such as naphtha, mineral spirits, and asphalt.

For the purposes of this document, petroleum liquids are classified into groups which are represented by crude oil, gasoline, jet naptha, distillate oil/kerosene, or residual oil. Evaporative emissions from marine vessel operations result from three processes: loading, ballasting, and transit. These processes are described in more detail below and in *Methodologies for Estimating Air Emissions from Three Non-Traditional Source Categories*. Although there may be certain ports where loading large marine tankers results in emissions greater than 100 tons per year (tpy) at a given facility, VOC emissions in most ports do not exceed 100 tpy. Methods discussed in this chapter apply to area sources only. Emissions for point source facilities, such as petroleum refineries, should be calculated using more detailed methods. Petroleum vessel loading, ballasting and their associated emissions are typically concentrated in urban coastal areas and ports on inland waterways. Transit emissions are based on the amount of time that the vessel is in an area.

2.2.1 LOADING LOSSES (SHIPS/OCEAN VESSELS AND BARGES)

Loading losses occur as organic vapors in "empty" cargo tanks are displaced to the atmosphere by the liquid being loaded into the tanks. These vapors are a composite of vapors formed in three ways:

- Vapors which are formed in the "empty" tank by evaporation of residual product from previous loads;
- Vapors transferred to the tank from a vapor balance system that was used when the previous load was being unloaded; and
- Vapors generated in the tank as the new product is being loaded.

Loading losses are usually the largest source of evaporative emissions from petroleum vessels (EPA, 1996). This activity usually only occurs at refineries or at the terminal at the end of the pipeline where the product is loaded for distribution. However, petroleum liquids shipped in "super tankers" may unload to barges in a harbor. In this situation, barge loading emissions occur along with ship transit and ballasting emissions. Barges (compartment depth 10 to 12 feet) exhibit higher emissions levels than ocean vessels which have greater compartment depth (approximately 40 feet).

2.2.2 BALLASTING LOSSES (SHIP/OCEAN VESSELS)

Ballasting losses are associated with the unloading of petroleum liquids at marine terminals and refinery loading docks. It is common practice to load several cargo tank compartments with sea water after the cargo has been unloaded. This water, called "ballast," improves the stability of the empty tanker during the subsequent voyage. Ballasting emissions occur as vapor-laden air in the empty cargo tank is displaced to the atmosphere by ballast water being pumped into the tank. Ballasting practices will vary. If the vessel being ballasted is equipped with segregated ballasting tanks, ballasting will not result in emissions of VOC to the atmosphere. However, if the vessels being ballasted are not equipped with segregated ballasting tanks, then ballasting may range between 15 to 40 percent of the vessels' capacities (EPA, 1996).

2.2.3 Transit Losses (Ship/Ocean Vessels and Barges)

Transit losses are similar to breathing losses associated with petroleum storage. Transit loss is the expulsion of vapor from a vessel compartment through vapor contraction and expansion, which are the result of changes in temperature and barometric pressure. This loss may be accompanied by slight changes in the level of the liquid in the tank due to liquid expansion or contraction due to the temperature change. Some ships are equipped with controls for these losses.

2.3 FACTORS INFLUENCING EMISSIONS

VOC emissions from petroleum vessel loading, ballasting, and transit are influenced by several factors. Emissions are a function of the physical and chemical characteristics of both previous

12.2-2 EIIP Volume III

and new cargos. Emissions are also a function of the vessel size. Many U.S. harbors are too shallow to receive large tankers. Instead, these tankers must remain outside the harbor area and off-load their cargo to smaller vessels in a process known as lightering. Since most lightering occurs more than 30 miles offshore, emissions from these operations are well dispersed before they reach the land. Lightering operations that occur outside the inventory study area may not need to be included in the inventory. Preparers of inventories should check with policymakers, modelers, or other inventory clients to determine whether it is necessary to include offshore lightering emissions. If lightering emissions do need to be included in an inventory, estimating the potential emissions from loading or ballasting will reflect the same processes as those discussed in Sections 2.2.1 and 2.2.2 of this chapter.

VOC emissions are also a function of the method of vessel loading. In splash loading, the fill pipe dispensing the cargo is lowered only partway into the cargo tank, resulting in higher turbulence during loading and subsequent high levels of vapor generation and loss. On the other hand, in submerged loading, the fill pipe extends almost to the bottom of the cargo tank, thus controlling liquid turbulence, and resulting in much lower vapor generation than encountered during splash loading.

2.4 CONTROL TECHNIQUES

The U.S. Coast Guard administers regulations (33 CFR, Part 157) that apply to all vessels exceeding 150 gross tons and are either documented under U.S. laws or are foreign vessels that transfer cargoes at ports subject to the jurisdiction of the U.S., or otherwise enter or operate in the navigable waters of the United States. The only exceptions are for foreign ships that are simply passing through U.S. waters or are exempt by the Port and Tanker Safety Act, as amended. The Coast Guard rule requires that all affected ships must have segregated ballast tanks, which should eliminate emissions from ballasting for these ships. Vessels unaffected by the regulation should be considered potential sources of ballasting emissions.

Many states require controls on vessel loading. State and local rules should be investigated before collecting other data for this category. Cases exist where companies have agreed to install controls where none are required by Federal, state or local regulations. Inventory preparers should identify these instances.

Emissions from vessel loading can be controlled through loading practice or through control equipment. Submerged loading, in which the fill pipe opening is below the liquid surface level, reduces liquid turbulence and resulting vapor generation (EPA, 1996). Emissions from splash loading can also be reduced by restricting the loading rate until the fill pipe is submerged. This

practice reduces the liquid turbulence during the splash loading portion of the load cycle. When vessel loading is part of a lightering operation, vapor balancing may be used to transfer the vapor from the vessel being loaded to the vessel being unloaded. Emissions from vessel loading may also be controlled at terminals through vapor balance systems or with vapor control systems, such as carbon adsorption, refrigeration, or thermal destruction units. 1

Controls for emissions from ballasting include using segregated non-contaminated ballast tanks, or placing the ballast between hulls on double-hulled ships (33 CFR, Part 157).

Emissions during transit can be reduced through the use of an inert gas system that maintains a slight positive pressure on the tanks to minimize emissions and reduce the risk of explosions.¹

The use of any of these controls within the inventory area should be investigated before emissions are calculated.

12.2-4 EIIP Volume III

¹ Personal communication between Allen Ellet, Senior Environmental Consultant, BP Oil Company, and L. Adams, Eastern Research Group Inc., February 1998.

OVERVIEW OF AVAILABLE METHODS

3.1 EMISSION ESTIMATION METHODOLOGIES

This document does not present an alternative method of estimating emissions from marine vessels carrying petroleum liquids. The preferred method can be used for any type of marine vessel, traffic classification, crude oil or refined petroleum product type, and any area of the United States served by marine vessels.

3.1.1 VOLATILE ORGANIC COMPOUNDS

The preferred method for estimating VOC emissions from marine vessel loading, ballasting, and transit is based on estimates of amount and type of products transported to or from the inventory area by waterways as well as the traffic classification (import, domestic, internal upbound, etc.). Fuels and other petroleum liquids transported are classified into five major product types of significantly different densities, vapor pressures, and physical compositions and the types of losses (emission points) expected from a specific operation are determined based on the traffic classification identified above. Inventory preparers with detailed information about the products being handled in their inventory area can use *AP-42* equations for estimation calculations, after activity data has been collected. VOC emissions are estimated by multiplying the throughput by the appropriate emission factors corresponding to the type of loss occurring in a specific traffic classification.

3.1.2 HAZARDOUS AIR POLLUTANTS

Hazardous air pollutant (HAP) emissions from this source are assumed to be proportional to the HAP vapor phase weight concentrations of the petroleum liquid for which the emissions are being calculated.

3.2 DATA NEEDS

3.2.1 DATA ELEMENTS

Several data sources are available on the movement of crude oil and other petroleum products; tonnage shipped and received; and capacities of refineries and bulk terminals at the national, regional, Petroleum Administration for Defense (PAD) District, state and local levels.

The minimum data elements needed to calculate emission estimates for marine vessel loading, ballasting, and transit are as follows:

- Petroleum liquids by traffic classification shipped² by type and volume aggregated by vessel type;
- Petroleum liquid by traffic classification received³ by type and volume aggregated by vessel type;
- Petroleum liquid in transit through inventory area;
- Controls in place for all operations, and control effectiveness;
- Product type within each traffic classification;
- Information on transport situation (i.e., barge loading, ballasting, transit) inferred from the traffic classification; and
- Fraction of transit time spent in inventory area.

Traffic classifications will depend on the data source used. Examples used in this document are based on the publication *Waterborne Commerce of the United States*.⁴

As mentioned in Section 2 of this chapter, regulations administered by the U.S. Coast Guard require that large marine vessels contain organic vapors from ballasting. As a result, ships

12.3-2 EIIP Volume III

² Traffic classification shipped: Materials classified as shipments or outbound are moved from the subject port to another location.

³ Traffic classification received: Materials classified as receipts or inbound are moved from another location to the subject port.

⁴ The publication can be obtained from the U.S. Army Corps of Engineers, New Orleans District, Waterborne Commerce Statistics Center, P.O. Box 61280, New Orleans, LA, 70161-1280. Tel. 504-862-1400; Waterborne commerce statistics may also be obtained on the internet from the Waterborne Commerce Statistics Center Wide World Web site at http://www.wrc-ndc.usace.army.mil/ndc/wcsc.htm.

affected by this rule do not need to be included in estimates of emissions from ballasting. Ballasting emissions from smaller vessels will need to be investigated.

3.2.2 Point Source Corrections

Although there are certain ports where handling of crude oil and other petroleum products may result in large emissions, annual VOC emissions at most ports would not exceed 100 tons. As a result, emissions from marine vessel loading and other operations generally should be considered area sources. Some areas may have petroleum refineries where vessel loading operations have been accounted for as point sources. If so, the area source emissions estimating methodology should be designed to not double-count any sources that have been inventoried as point sources.

3.2.3 APPLICATION OF CONTROLS

Control techniques for loading, ballasting and transit are discussed in Section 2.4 of this chapter. Rules will vary by locale and the size of the terminal or vessel. Inventory preparers should investigate the rules in place in the inventory area, and determine if those rules apply to the smaller sources that make up an area source inventory. Air agencies, local port authorities, and marine vessel operators should be contacted about rules that apply in the inventory area. In addition to controls that are put in place because of rules, inventory preparers should identify instances of controls that are not required, but still used.

Air pollution control regulations in Louisiana and Pennsylvania require that marine loading facilities serving ships and/or barges loading crude oil, gasoline, or volatile organic compounds be equipped with a vapor collection system designed to collect the organic compounds vapors displaced from ships and/or barges during loading. The vapors are then processed by recovery and/or destruction systems such that uncontrolled emissions are reduced by at least 90 percent by weight. Pennsylvania air laws also require that by September 28, 1996, a minimum of 65 percent of the total volume of receipt of crude oil and gasoline during a specified period be delivered to a facility in vessels which do not ballast, such as barges, or in vessels which do not emit VOC when ballasted, such as tankers using segregated ballast tanks.

Chapter 1 of this volume, the *Introduction to Area Source Emission Inventory Development*, provides general guidance for determining and applying rule effectiveness (RE) for a source category. In addition, the EPA document *Procedures for Estimating and Applying Rule Effectiveness in Post-1987 Base Year Emission Inventories for Ozone and Carbon Monoxide State Implementation Plans* provides more detailed information on RE (EPA, 1989).

3.2.4 SPATIAL ALLOCATION

The preferred method estimates emissions from loading, ballasting, and transit at the study region level. Emissions from these operations are concentrated in coastal areas, areas surrounding the Great Lakes, and areas adjacent to ports on inland waterways.

3.2.5 TEMPORAL RESOLUTION

Seasonal Apportioning

Emissions from loading, ballasting, and transit of petroleum liquids from marine vessels are expected to be spread evenly over time, with little or no seasonal variations. Seasonal variations are expected in those areas where wintertime frozen waters make ports inaccessible, such as the Great Lakes region.

Alternatively, temporal allocation of vessel loading, ballasting, and transit emissions can be accomplished by (1) obtaining detailed monthly activity data for the port in question and applying these data to the estimation equation, or (2) by apportionment factors based on use of the various products. The second method would capitalize on data which should already exist from area/mobile source inventory efforts (e.g., monthly or seasonal allocation of motor fuel; consumption and/or vehicle miles traveled; home heating fuels; aircraft fuels, etc.).

VOC emissions from these marine vessel operations vary due to changes in temperature as well as vapor pressure. Equations are available that account for such variations. However, this source category generally accounts for a relatively small portion of the overall area inventory.

Daily Resolution

Vessel loading and unloading operations are assumed to occur on a daily basis, seven days a week.

3.3 PROJECTING EMISSIONS

Projecting emissions from petroleum vessel loading, ballasting, and transit requires information on anticipated changes in demand for those products and prices, as well as changes in storage capacity at ports and harbors. If no information is available, the inventorying agency can assume no changes to the existing level of activities. Alternatively, historic activity at the ports in the inventory area would be the best source of data for projecting future vessel activity.

12.3-4 EIIP Volume III

PREFERRED METHODS FOR ESTIMATING EMISSIONS

4.1 Preferred Method

The preferred method for estimating emissions from petroleum vessel loading, ballasting, and transit is described below. This method has limitations because the data that are needed are often not available. The method is intended to produce representative area source emissions estimates without requiring the expenditure of an unreasonable amount of resources to fill information gaps. However, it is recommended that, as a first step, inventory preparers identify controls that are in use in the area, and determine if emissions are primarily inventoried as part of the point source inventory. See Sections 2.4 and 3.2.3 of this chapter for more information about controls. Because some controls may eliminate emissions from certain processes and vessels altogether, data collection can be reduced to only those vessels and processes that are actually creating emissions. The steps of the methodology are as follows:

4.1.1 DETERMINATION OF AMOUNT OF PETROLEUM LIQUIDS TRANSPORTED TO OR FROM THE INVENTORY REGION

Determine the amount and type of petroleum liquids transported to or from the inventory region by waterway. The publication *Waterborne Commerce of the United States*¹ can be used to obtain data on the movements of commodities and vessels at individual ports and harbors and on individual waterways and canals of the United States. Both foreign and domestic commerce are included. Other sources of potentially useful information are the *Petroleum Supply Annual*, ² *Petroleum Storage and Transportation* (DOE, 1989), publications from the U.S. Maritime Administration (U.S. Maritime Administration, 1985), and the *Petroleum Terminal*

¹ The publication can be obtained from the U.S. Army Corps of Engineers, New Orleans District, Waterborne Commerce Statistics Center, P.O. Box 61280, New Orleans, LA, 70161-1280. Tel. 504-862-1400; Waterborne commerce statistics may also be obtained on the internet from the Waterborne Commerce Statistics Center Wide World Web site at http://www.wrc-ndc.usace.army.mil/ndc/wcsc.htm.

The *Petroleum Supply Annual* can be obtained from the Energy Information Administration, Department of Energy, Washington, DC.

Encyclopedia.³ Estimates of percentage of each fuel type carried by each type of vessel are available from National or Regional Petroleum Administrations for Defense district, or the state.

The New Orleans District Data Request Office of the U.S. Army Corps of Engineers also handles special requests (at a cost), for water commerce statistics such as port- and harbor-specific information regarding shipping and receiving operations. Available data include the following:

- Crude oil and other petroleum products shipped and received at each harbor aggregated by fuel type of vessel (i.e., tankers versus barges);
- Refinery receipts of crude oil and petroleum products by type of vessel; and
- Refinery shipments of crude oil and petroleum products by type of vessel.

In some cases, only one shipping company ships specific products to and from certain locations. If the Data Request Center were to reveal the tonnage for each product shipped, the Confidential Business Information for that particular company may be compromised. In this situation the Data Request Center prefers to submit the data as lump sum totals without specifying the tonnage to each destination.

4.1.2 IDENTIFICATION OF EMISSION POINTS

Use Table 12.4-1 to identify the emission points for each traffic classification. Determine emission points for all petroleum commodity types. Additional traffic classifications may exist. Classifications listed here represent the most likely emission process assignments. Table 12.4-1 is based on the following assumptions:

- All traffic involves transit emissions;
- Loading (ship, vessel, barge) emissions only result from export, shipment, and outbound traffic;
- Ballasting emissions only result from import and receipts traffic where the return voyage requires balancing;
- Through traffic results only in transit emissions; and

12.4-2 EIIP Volume III

³ A periodic report from Salsby/Wilson Press, Houston, Texas.

• Barge loading emissions result only from exports and shipments traffic in shallower waterways (e.g. internal, lakeside waterways). Inventory preparers should investigate the use of barges and ships in their area.

The emission points presented in Table 12.4-1 are defined based on the traffic type definitions presented in the U.S. Army Corps of Engineers' *Waterborne Commerce of the United States*. Definitions of the traffic classifications can be found in that document. Loading operations (ship/vessel loading and barge loading) occur when the commodity is moved from the subject port to another port or location. Other traffic is assumed to be either traffic that has originated from another port or location and represents an unloading operation, or through traffic that does not stop at the port/waterway. One exception to this rule is intra-port or intra-waterway traffic which is loaded and unloaded in the subject waterway.

Unloading operations do not result in emissions from the vessel itself. Unloading operations only result in emissions counted as part of this source category if ballasting occurs to the vessel being unloaded. Otherwise the emissions that result due to the loading of the receiving tank or truck are counted as the source category covering emissions from loading tanks or trucks. Unless the receiving vessel is another marine vessel, loading of the tank or truck would not be considered marine loading and would not be part of this area source category.

4.1.3 CLASSIFICATION OF PETROLEUM PRODUCTS BY FUEL TYPE

Classify the petroleum liquids transported in the inventory region into five fuel type classifications using Table 12.4-2. If inventory data quality objectives require more detailed emission estimates, the inventory preparer may want to use the equations for calculating emissions from *AP-42*, Section 5.2, Transportation and Marketing of Petroleum Liquids, and portions of *AP-42*, Section 7.1, Liquid Storage Tanks, including Table 7.1-2, Properties of Selected Petroleum Liquids. The equations in *AP-42* require considerably more data collection than the data collection discussed in this chapter. The inventory preparer may want to consider the costs and benefits of using the more detailed approach, and may want to use the *AP-42* equations on a small subset of products that will most make the most significant improvement to the overall estimate, and use the emission factors presented here for the remaining products.

TABLE 12.4-1 EMISSION POINTS FOR PETROLEUM VESSEL TRAFFIC CLASSIFICATIONS

Traffic Classification ^a	Ship/Ocean Vessel Loading	Barge Loading ^{b,c}	Ballasting ^c	Transit
Foreign Imports			X	X
Foreign Exports	X			X
Foreign Intratransit Merchandise				X
Foreign Through Upbound				X
Foreign Through Downbound				X
Canadian Exports	$\mathbf{X}^{ ext{d}}$	X^{d}		X
Canadian Imports			X^{d}	X
Canadian Through Upbound				X
Canadian Through Downbound				X
Coastwise Receipts			X	X
Coastwise Shipments	X			X
Coastwise Through Upbound				X
Coastwise Through Downbound				X
Lakewise Receipts			X	X
Lakewise Shipments		X		X
Internal Receipts			X	X
Internal Shipments		X		X
Internal Inbound Upbound			X	X
Internal Inbound Downbound			X	X
Internal Outbound Upbound		X		X
Internal Outbound Downbound		X		X
Internal through Upbound				X
Internal through Downbound				X
Internal Intra-waterway Upbound		X	X	X
Internal Intra-waterway Downbound		X	X	X
Internal Intraport		X	X	X
Intra-territory Shipments		X		X
Intra-territory Receipts			X	X

These classifications are used in the *Waterborne Commerce of the United States*, U.S. Army Corps of Engineers, Waterborne Commerce Statistics Center, New Orleans, LA. Barges may not be used at all ports by the indicated traffic classification. Inventory preparers should research ballasting practices in their area to identify the traffic classifications where ballasting actually occurs. Inventory preparers should research the use of barges and ships in their area.

TABLE 12.4-2

PRODUCT TYPE CLASSIFICATIONS FOR COMMON PETROLEUM VESSEL COMMODITIES^a

Petroleum Vessel Commodity	Product Type Classification
Crude petroleum	Crude oil
Gasoline	Gasoline
Kerosene	Distillate oil
Distillate fuel oil	Distillate oil
Residual fuel oil	Residual oil
Lube oil and greases	Distillate oil
Petro. jelly and waxes	Distillate oil
Naphtha and solvents	Jet naphtha
Asphalt, tar, and pitch	Residual oil
Petroleum coke	Residual oil
Liquid natural gas	Gasoline
Petroleum products not elsewhere classified	Jet naphtha

^a These classifications were determined by approximately matching the density, vapor pressure, and physical composition of the commodities to the five product types. The product types match available AP-42 emission factors.

EIIP Volume III 12.4-5

An example of how data from the *Waterborne Commerce* document can be compiled for one large waterway is shown in Example 12.4-1.

Example 12.4-1:

Data from Example Area A, an area where large amounts of petroleum liquids are handled, is listed in Appendix A as it is provided in the *Waterborne Commerce of the United States*. Shipments and receipts of commodities are listed by product type and traffic classification. Definitions of traffic classifications can be found in the *Waterborne Commerce* document. For an area source inventory, the information needs to be compiled first by traffic classifications representing similar processes, and then by product types that can be linked to existing emission factors. For this example, these steps are accomplished using a spreadsheet. The first step, shown in Table 12.4-3, is to enter the data into the spreadsheet so it can be sorted by traffic classification and product type.

Table 12.4-4 shows the data further combined into groups based on traffic classification and sorted by product types that will match *AP-42* emission factors. Table 12.4-1 can be used to match traffic classifications and AP-42 processes, e.g. ship loading or barge loading. Note that based on local information, only foreign and Canadian and coastwise receipt categories were subject to ballasting.

4.1.4 ESTIMATION OF TRANSIT EMISSIONS

For transit emissions, estimate the average time traffic is in the inventory area. Specific data may be difficult to obtain. The best resource for this information may be the local port authorities.

4.1.5 CORRECTION FOR POINT SOURCE EMISSIONS

It is possible for some marine loading operations, such as those at large petroleum refineries operating their own port, to be included in point source inventories. To make the double-counting correction, the material throughputs from specific point source SCCs should be totaled and subtracted from the total area source material transferred. Area source emissions should then be estimated based on this corrected material transferred amount.

If the point source material throughputs are not available, the correction can be made at the emissions level (subtract total emissions from specific point source SCCs from total area source emissions). Emissions from vessel loading/unloading operations at facilities such as petroleum refineries located in the inventory area should be deducted from the area source totals. Point source SCCs may include 40600231 through 40600259. Additional point source SCCs may exist, so the point source inventory should be carefully reviewed.

12.4-6 EIIP Volume III

Product Code	Commodity Name	AP-42 Product Type Class	Foreign & Canadian Total	Foreign & Canadian Imports	Foreign & Canadian Exports	Coastwise Total	Coastwise Receipts	Coastwise Shipments	Coastwise Through	Internal Total	Internal Inbound	Internal Outbound	Internal Through	Internal Intra
2100	Crude Petroleum	Crude	38,744	38,744	0	75	72	4	0	5,654	841	575	4,205	33
2211	Gasoline	Gasoline	518	0	518	1,654	21	1,633	0	5,294	626	940	3,536	192
2221	Kerosene	Distillate	0	0	0	0	0	0	0	290	0	131	159	0
2330	Distillate Fuel Oil	Distillate	20	12	8	322	83	239	0	4,494	570	1,398	2,484	72
2340	Residual Fuel Oil	Residual	232	72	160	144	59	85	0	5,613	541	1,947	2,920	205
2350	Lube Oil & Grease	Distillate	737	690	47	570	256	314	0	1,112	27	356	726	3
2410	Petro Jelly & Waxes	Distillate	0	0	0	0	0	0	0	56	0	0	56	0
2429		Jet Naphtha	177	155	22	27	27	0	0	2,119	421	373	1,109	216
2430	Asphalt, Tar & Pitch	Residual	43	2	41	19	0	0	19	1,075	14	23	1,038	0
2540	Petroleum Coke	Residual	3,676	241	3,435	0	0	0	0	776	446	64	261	4
2640	Liquid Natural Gas	Gasoline	158	131	27	0	0	0	0	552	239	55	255	4
2990		Jet Naphtha	0	0	0	7	0	7	0	624	101	226	284	15

^a All commodity amounts in one thousand tons

TABLE 12.4-4

PROCESS/ PRODUCT CATEGORIES^a

			Ship loading		Barge Loading		Ballasting		Transit		
AP-42 Product Type Class	Product Code	Commodity Name		Coastwise Shipments	Internal Outbound	Internal Intra	Foreign & Canadian Imports	Coastwise Receipts	Foreign & Canadian Total	Coastwise Total	Internal Total
Crude	2100	Crude Petroleum	0	4	575	33	38,744	72	38,744	75	5,654
Distillate	2330	Distillate Fuel Oil	8	239	1,398	72	12	83	20	322	4,494
Distillate	2350	Lube Oil & Grease	47	314	356	3	690	256	737	570	1,112
Distillate	2221	Kerosene	0	0	131	0	0	0	0	0	290
Distillate	2410	Petroleum Jelly and Waxes	0	0	0	0	0	0	0	0	56
Gasoline	2640	Liquid Natural Gas	27	0	55	4	131	0	158	0	552
Gasoline	2211	Gasoline	518	1,633	940	192	0	21	518	1,654	5,294
Jet Naphtha	2990	Petroleum Prod., NEC	0	7	226	15	0	0	0	7	624
Jet Naphtha	2429	Naphtha & Solvents	22	0	373	216	155	27	177	27	2,119
Residual	2340	Residual Fuel Oil	160	85	1,947	205	72	59	232	144	5,613
Residual	2430	Asphalt, Tar and Pitch	41	0	23	0	2	0	43	19	1,075
Residual	2540	Petroleum Coke	3,435	0	64	4	241	0	3,676	0	776

^a All commodity amounts in one thousand tons

4.1.6 ESTIMATION OF EMISSIONS FROM PETROLEUM VESSELS

Use the estimates of petroleum liquids, grouped by traffic classification and sorted by product types, and the emission factors in Table 12.4-5 to estimate total VOC emissions from petroleum vessels for each of the five types of petroleum liquids (p) at each emission point. It should be noted that these factors are for dispensed product at 60° F and can be adjusted for significantly different conditions using original derivation methods in AP-42. It should also be noted that some emission factors may not apply to a particular port, e.g., barge loading or ballasting, may not take place.

In Section 2.2.2 of this chapter, ballasting practices are discussed. If ballasting only occurs using segregated ballast tanks, it is not necessary to estimate ballasting emissions. However, if ballasting uses the empty cargo tank, emissions will occur, and must be calculated. Note that the calculation for ballasting emissions in the equation includes a correction term of 0.30. This correction term reflects the practice of loading a ship or barge at some fraction of capacity when ballasting. Emission estimates will be improved if local information about typical percentages can be located and used. The correction term presented here represents a conservative assumption.

Apply any control efficiency to the appropriate terms in Equation 12.4-1, or Equation 12.4-2 can be used to apply control efficiency.

$$PV_{p} = [(SOEF_{p} \times PP_{S,p}) + (BREF_{p} \times PP_{B,p}) + (BLEF_{p,U} \times 0.30 \times PP_{BL,p}) + (TREF_{p} \times PP_{T,p})] \div 2000$$
 (12.4-1)

where:

 $PP_{B,p}$

PV_p = Total VOC emissions from petroleum vessel loading, ballasting, and transit for each of the petroleum liquids (p) transported: crude oil, gasoline, kerosene, distillate oil, and residual oil (tons)

SOEFp = Ship/ocean vessel loading emission factor (pounds VOC per 1,000 gallons transferred)

 $PP_{S,p}$ = Amount of petroleum liquid (p) loaded into ships and ocean vessels in the inventory region (1,000 gallons)

BREF_p = Barge vessel loading emission factor (pounds VOC per 1,000 gallons transferred)

= Amount of petroleum liquid (p) loaded into barges in the inventory region (1,000 gallons)

BLEF_p = Ballasting emission factor (pounds VOC per 1,000 gallons water ballasted)
PP_{BL,p} = Amount of petroleum liquid (p) unloaded from vessels that are ballasted
(1,000 gallons)

EIIP Volume III 12.4-9

TREF_p = Vessel transit emission factor (pounds VOC per week per 1,000 gallons transferred)

 $PP_{T,p}$ = Amount of petroleum liquid (p) transported by marine vessels in the inventory region (1,000 gallons)

TABLE 12.4-5

Uncontrolled VOC Emission Factors For Petroleum Carrying Marine **VESSELS (EPA, 1996)**

Petroleum Liquid	Ship/Ocean Vessel Loading(PoundsVOCper 1,000 gallons Transferred)	Barge Loading (Pounds VOC per 1,000 gallons Transferred)		Transit(PoundsVOCper week per 1,000 gallons Transported)
Crude Oil	0.61	1	1.1 ^b	1.3
Gasoline	1.8 ^b	3.4 ^b	0.8^{b}	$2.7^{\rm b}$
Jet Naphtha/ Other	0.5	1.2	NA	0.7
Distillate Oil/Kerosene	0.005	0.012	NA	0.005
Residual Oil	4 x 10 ⁻⁵	9 x 10 ⁻⁵	NA	3 x 10 ⁻⁵

^a It may not be necessary to estimate ballasting emissions. See Section 3, of this chapter, Data Elements for discussion.

If controls exist, then control efficiency can be calculated:

$$PP_{C} = PP_{U} * (1 - CE/100)$$
 (12.4-2)

where:

PP_C = Controlled emissions (10115) PP_U = Uncontrolled emissions (tons) CE = Control efficiency (%)

12.4-10 EIIP Volume III

b These are AP-42 "typical overall situation" factors; various additional factors related to specific types of service can be found in AP-42. In addition, AP-42 equations could be used, if necessary, to calculate emission factors for specific compounds, given values for true vapor pressures and average liquid molecular weights.

Data obtained from sources such as the *Waterborne Commerce of the United States* are typically provided in terms other than 1,000 gallons (Mgal) as is required in Equation 12.4-1 and must be converted. Equation 12.4-3 can be used to convert units from 1,000 ton (Mtons) to Mgal.

$$PP_{V} = (PP_{m}/d) * 2,000 \text{ lb/ton} * Mgal/1,000 \text{ gallons} * 1,000 \text{ tons/Mtons}$$
 (12.4-3)

where:

PP_v = Amount of petroleum liquid (Mgal) PP_m = Amount of petroleum liquid (Mtons) d = Density of petroleum liquid; see Table 7.1-2 in AP-42 (lb/gallon)

Example 12.4-2 illustrates the calculations used to estimate emissions from tons of fuel.

EIIP Volume III 12.4-11

Example 12.4-2

The inventory area had an annual throughput of gasoline from vessel loading, barge loading, and transit operations as indicated below:

Operation	Throughput (1,000 tons)
Vessel loading	2,178
Barge loading	1,191
Ballasting	152
Transit	8,176

Using the gasoline density factor found in AP-42, Table 7.1-2 (5.6 lb/gal), and Equation 12.4-3, the mass throughputs are converted to volumetric throughputs. Vessels loading throughputs are converted by:

$$PP_v = [2,178 \text{ Mtons/}(5.6 \text{ lb/gal})] * \frac{2,000 \text{ lb}}{\text{ton}} * \frac{\text{Mgal}}{1,000 \text{ gal}} * \frac{1,000 \text{ tons}}{\text{Mtons}}$$

The results of the calculation are shown below:

Conversion of Mass Throughputs to Volumetric Throughputs							
Operation	Equation 12.4-1 Parameter	Throughput (Mtons)	Throughput (Mgal)				
Vessel loading	$\operatorname{PP}_{\operatorname{S,gas}}$	2,178	777,857				
Barge loading	$\mathrm{PP}_{\mathrm{B,gas}}$	1,191	425,357				
Ballasting	$\mathrm{PP}_{\mathrm{BL,gas}}$	1,213	54,286				
Transit	$\operatorname{PP}_{\operatorname{T.gas}}$	8,176	2,920,000				

12.4-12 EIIP Volume III

Example 12.4-2 (Continued)

For vessel loading operations, 90 percent of the total throughput was loaded at terminals with a control system of 95 percent efficiency. According to the local port authorities, transit time in the inventory area is two days (2/7 of a week). Emissions for each emission point are calculated using Equation 12.4-1 and the emission factors from Table 12.4-5. In this example, emissions for each emission point are calculated separately and then totaled. Note that CE is applied to vessel loading emissions, and transit emissions are apportioned to two days per week by multiplying emissions by 2/7.

Vessel Loading emissions are calculated:

$$PV_{gas} = [1.8 \text{ lb VOC/Mgal} * 777,857 \text{ Mgal/yr}) * (0.10 + (0.9 * \left(1 - \frac{95}{100}\right)] \div 2,000 \text{ lb/ton}$$
$$= 102 \text{ tons/yr}$$

Barge Loading emissions are calculated:

$$PV_{gas} = [3.4 lb VOC/Mgal * 425,357 Mgal/yr)] \div 2,000 lb/ton$$
$$= 723 tons/yr$$

Ballasting emissions are calculated:

$$PV_{gas} = [0.8 lb VOC/Mgal*54,286 Mgal/yr)*0.30] \div 2,000 lb/ton$$

$$= 7 tons/yr$$

Transit emissions are calculated:

$$PV_{gas} = (2.7 \text{ lb VOC/Mgal} * 2,920,000 \text{ Mgal/yr} * 2/7 \text{ wk}) \div 2,000 \text{ lb/ton}$$

= 1,128 tons/yr

EIIP Volume III 12.4-13

Example 12.4-2 (Continued)

Total VOC emissions are calculated as follows:

Total VOC =
$$102 \text{ tons/yr} + 723 \text{ tons/yr} + 7 \text{ tons/yr} + 1,128 \text{ tons/yr}$$

= $1,957 \text{ tons/yr}$

Contributions from the point source inventory are 82 tons/yr VOC. The total VOC emissions in the area source inventory are:

1,957 tons/yr - 82 tons/yr = 1,875 tons/yr

12.4-14 EIIP Volume III

ALTERNATIVE METHODS FOR ESTIMATING EMISSIONS

No alternative methods are known to exist, nor are any necessary since the preferred method and data associated with it can be used for any type of vessel, any type of traffic, any type of fuel, and any area of the United States serviced by petroleum vessels.

This page is intentionally left blank.

12.5-2 EIIP Volume III

QUALITY ASSURANCE/ QUALITY CONTROL

Data collection and handling for the marine vessel loading, ballasting, and transit source category should be planned and documented in the Quality Assurance Plan. In particular, material type assignments and emission estimation calculations should be reviewed as part of the QA/QC procedures. Refer to the discussion of inventory planning and QA/QC in Chapter 1, *Introduction to Area Source Emission Inventory Development*, of this volume, and the QA volume (VI) of the EIIP series.

6.1 EMISSION ESTIMATE QUALITY INDICATORS

One method is provided in this chapter for estimating emissions from marine vessel loading, ballasting, and transit. Data collection for this source category involves identifying the most suitable data source from those listed in Section 4 of this chapter, and compiling the information. Although data collection for this category can require a significant amount of effort, the quality of the activity data is high, and the effort required may be justified by the importance of the estimated emissions in areas where there is a significant amount of marine vessel loading, ballasting, and transit.

6.1.1 DATA ATTRIBUTE RATING SYSTEM (DARS) SCORES

The DARS scores for the preferred method are summarized in Table 12.6-1. A range of scores is provided to account for differences in the implementation of the method. Lower activity scores are shown for activity data that are not drawn from records collected specifically for the inventory area. This would be the case if specific product data are not available for the inventory area and the tonnage of each product loaded or unloaded in the inventory area must be apportioned from regional data. Higher DARS scores than those assigned in Table 12.6-1 could be assigned if the equations from AP-42 are used, rather than emission factors that have been derived from the equations.

Lower emission factor scores reflect the necessary simplifications that must be made for an area source method. The first simplification is the use of emission factors developed from the equations provided in *AP-42*. Assumptions have been made concerning the fuel type vapor pressure and the molecular weight of vapors, which are addressed in the source specificity score,

and average annual temperature, which is addressed in the spatial congruity score. The emission factor measurement scores will vary depending on whether the product is actually the product type for which the emission factor was developed, or a similar product that has been grouped into that product classification (see Table 12.4-1). Variability in local practices affect the spatial congruity score. Seasonal temperature differences and potential changes in equipment and filling practices since the latest update of the emission equations and parameters in *AP-42* affect the temporal congruity score.

TABLE 12.6-1
PREFERRED METHOD: DARS Scores

	Scores					
Attribute	Factor	Activity	Emissions			
Measurement	0.3 - 0.5	0.9	0.27 - 0.45			
Source Specificity	0.7 - 0.9	0.7 - 0.9	0.49 - 0.81			
Spatial Congruity	0.5	0.7 - 1.0	0.35 - 0.5			
Temporal Congruity	0.5	0.9 - 1.0	0.45 - 0.5			
Composite Scores	0.5 - 0.6	0.80 - 0.95	0.39 - 0.57			

6.1.2 Sources of Uncertainty

There are several sources of uncertainty in estimating emissions from this source category. When the method provided in this chapter is used, activity data are collected, the data may be apportioned to reflect activity in the inventory area, and amounts of some materials are grouped with similar material types into product classifications. Each of these steps will have some associated uncertainty, and the uncertainty cannot be quantified.

An additional source of uncertainty comes from using emission factors rather than equations that use a number of parameters. In this case, the sensitivity of the equations to different parameters could be quantified using typical sensitivity analysis techniques.

12.6-2 EIIP Volume III

DATA CODING PROCEDURES

The codes shown in Table 12.7-1 are recommended for the marine vessel loading, ballasting, and transit category. The codes that identify the type of petroleum product are preferred, corresponding to the five possible PV_p totals from the emission estimation equation.

TABLE 12.7-1

AMS CODES FOR THE MARINE VESSEL LOADING, BALLASTING AND TRANSIT CATEGORY (EPA, 1992)

Category Description	Process Description	AMS Code	Units
Petroleum and Petroleum Product	Crude Oil	25-05-020-030	1000 Gallons Transferred
Transport: Marine Vessels	Residual Oil	25-05-020-060	1000 Gallons Transferred
	Distillate Oil	25-05-020-090	1000 Gallons Transferred
	Gasoline	25-05-020-120	1000 Gallons Transferred
	Kerosene	25-05-020-180	1000 Gallons Transferred

7.1 Process and Control Codes

Table 12.7-2 shows the control device codes that may be used in the AIRS Area and Mobile Source Subsystem (AMS) to indicate the level of control used for this source in the inventory region. Federal, State, and local regulations can be used as guides to estimate the type of control used and the level of efficiency that can be achieved. Be careful to apply only the regulations that specifically include area sources. Control of emissions from petroleum vessel loading, ballasting, and transit may include the use of vapor recovery, techniques that minimize evaporation, and techniques that collect and destroy organic vapors. Other control devices may be used for these operations. The efficiencies of known control devices must be applied to the individual segments of the emission estimation equation by creating separate totals for each emission type known to be at a different control level.

The "099" control code can be used for miscellaneous control devices that do not have a unique identification code. The "999" code can be used for a combination of control devices where only the overall control efficiency is known.

TABLE 12.7-2

AIRS CONTROL DEVICE CODES

Control Device	Code
Vapor Recovery System	047
Barometric Condenser	074
Submerged Filling	093
White Paint	095
Nitrogen Blanket	087
Conservation Vent	088
Refrigerated Condensers	047
Miscellaneous Control Device	099
Combined Control Efficiency	999

12.7-2 EIIP Volume III

REFERENCES

EPA. 1996. Compilation of Air Pollution Emission Factors - Volume 1: Stationary Point and Area Sources. Fifth Edition, AP-42. U.S. Environmental Protection Agency, Office of Air Quality Planning and Standards. (GPO 055-000-00251-7). Research Triangle Park, North Carolina.

EPA. 1993. *Methodologies for Estimating Air Emissions from Three Non-Traditional Source Categories: Oil Spills, Petroleum Vessel Loading and Unloading, and Cooling Towers*. U.S. Environmental Protection Agency, Office of Research and Development. EPA-600/R-93-063 (NTIS PB93-181592). Washington, DC.

EPA. 1992. AIRS Area and Mobile Source Category Codes. U.S. Environmental Protection Agency, Office of Air Quality Planning and Standards. Research Triangle Park, North Carolina.

EPA. 1989. Procedures for Estimating and Applying Rule Effectiveness in Post-1987 Base Year Emission Inventories for Ozone and Carbon Monoxide State Implementation Plans. U.S. Environmental Protection Agency. Research Triangle Park, North Carolina.

DOE. 1989. Petroleum Storage and Transportation, Volume II: System Dynamics. Nation Petroleum Council, U.S. Department of Energy. Washington, DC.

U.S. Maritime Administration. 1985. *Domestic Waterborne Trade of the U.S.* U.S. Maritime Administration, Office of Domestic Shipping. Washington, DC.

This page is intentionally left blank.

12.8-2 EIIP Volume III

Appendix A

Example Waterborne Commerce Data

EXAMPLE AREA A

Section Included: Gulf of Mexico to turning basins at West Port Arthur, Beaumont, and Orange, TX, about 85.8 miles; Adams Bayou Channel, about 1.6 miles; and Cow Bayou Channel, about 7 miles. Controlling Depth: Sabine Pass Channel, TX, 40 feet; Port Arthur, TX, 37 feet; Beaumont, TX, 39 feet; extension to Bethlehem Steel Shipyard, 32 feet; Orange, TX, 27 feet except channel around Harbor Island, 20 feet; Adams Bayou Channel, 9 feet; and Cow Bayou Channel, 8 feet. Project Depth: Sabine Pass Harbor, TX, 40 to 42 feet; Port Arthur, TX, 40 feet; Beaumont, TX, 40 feet except turning basin, 34 feet, and extension to Bethlehem Steel Shipyard, 30 feet; Orange, TX, 30 feet except channel around Harbor Island, 25 feet, Adams Bayou, 12 feet, and Cow Bayou, 13 feet, mean low tide.

Comparative Statement of Traffic (thousand tons)

Year	Total	Year	Total
1986	75,943	1991	84,213
1987	79,742	1992	88,348
1988	89,091	1993	95,191
1989	96,564	1994	99,675
1990	90,819	1995	103,254

Freight Traffic, 1995 (thousand tons)

	(,			
	Commodity	Total	Fore	eign	Can	nadian
1	Commodity	Total	Imports	Exports	Imports	Exports
Total, a	all commodities	49,124	40,724	8,178	167	55
Total p	etroleum and petroleum products	44,305	39,886	4,203	161	55
Sub 2100	ototal crude petroleum crude petroleum	38,744 38,744	38,583 38,583		161 161	
Sub 2211 2330 2340 2350 2429	gasoline gasoline distillate fuel oil residual fuel oil lube oil & greases naphtha & solvents	5,562 518 21 232 737 177	1,303 	4,203 518 8 160 47 22		55
2430 2540 2640	asphalt, tar & pitch petroleum coke liquid natural gas	43 3,676 158	2 241 131	41 3,380 27		55
Total cl	hemicals and related products	757	33	724		
Sub 3190	ototal fertilizers fert. & mixes nec	12 12		12 12		
Sub 3211 3212 3219 3220 3240 3260 3275 3276 3281 3282 3285 3286 3291	acyclic hydrocarbons acyclic hydrocarbons benzene & toluene other hydrocarbons alcohols nitrogen func. comp organic comp. nec inorg. elem., oxides, & halogen salts metallic salts radioactive material pigments & paints perfumes and cleansers plastics	745 26 44 104 103 10 25 0 430 0 0	33 22 	712 4 44 100 100 10 22 430 0		
3297 3298	pesticides chemical additives wood & resin chem.	1 0	0	1 0		

		Гои	-:	Canadian		
Commodity	Total		eign Exports		inadian Exports	
Total crude materials, inedible except fuels	727	Imports 1 441	Exports	Imports		
Subtotal forest products, wood and chips 4161 wood chips 4170 wood in the rough 4189 lumber	231 224 0 6	6 0 0 6	224 224 0			
Subtotal pulp and waste paper 4225 pulp & waste paper	62 62		62 62			
Subtotal soil, sand, gravel, rock and stone 4322 limestone 4331 sand & gravel	432 30 402	432 30 402				
Subtotal iron ore and scrap 4420 iron & steel scrap	2 2	2 2				
Subtotal non-ferrous ores and scrap 4680 non-ferrous scrap	0 0	0 0				
Subtotal other non-metal. min. 4900 non-metal. min. nec	0 0		0 0			
Total primary manufactured goods	549	333	211	6		
Subtotal paper products 5120 paper & paperboard 5190 paper products nec	22 21 0	0 0 0	21 21 0			
Subtotal lime, cement and glass 5290 misc. mineral prod.	2 2	0 0	1 1			
Subtotal primary iron and steel products 5312 pig iron 5320 i&s primary forms 5330 i&s plates & sheets 5360 i&s bars & shapes 5370 i&s pipe & tube	313 2 262 1 3 1	304 1 256 1 0	4 0 3 3 1	6 6		
5390 primary i&s nec	45	45				
Subtotal primary non-ferrous metal products 5422 aluminum 5429 smelted prod. nec 5480 fab. metal products	2 1 0 1	1 1 0	1 0 0 1			
Subtotal primary wood products 5540 primary wood prod.	211 211	27 27	183 183			
Total food and farm products	2,778	30	2,748			
Subtotal grain 6241 wheat 6344 corn 6442 rice 6447 sorghum grains	1,733 1,486 0 20 227		1,733 1,486 0 20 227			
Subtotal oilseeds 6522 soybeans 6590 oilseeds nec	513 513 0		513 513 0			
Subtotal vegetable products 6653 vegetable oils 6654 vegetables & prod.	15 1 14		15 1 14			

12.A-2

	Commodity	Total	For	eign	Car	nadian
	Commodity	Total	Imports	Exports	Imports	Exports
Suk 6746 6747 6782	ototal processed grain and animal feed wheat flour grain mill products animal feed, prep.	507 385 95 27	27 27	480 385 95		
Subt 6858 6871 6885 6889 6893	total other agricultural products fruit juices coffee alcoholic beverages food products nec cotton	11 0 3 0 8 0	3 0 3 1 1	7 0 0 7 0		
Tota and pro	al all manufactured equipment, machinery oducts	8	2	6		
7110 7120 7210 7220 7230	Machinery (not elec) electrical machinery vehicles & parts air craft & parts ships & boats	3 3 0 0 1	1 0 0	2 2 0 0 1		
7400 7500 7600 7900	manufac. wood prod. textile products rubber & plastic pr. manufac. prod. nec	0 0 0 0	0 0 0 0	0 0 0		
Totalun	nknown or not elsewhere classified	0	0			
9900	unknownornec	0	0			
Ton- Foreign	-miles (x1000) a & Canadian	123,373	80,527	42,846	0	0

				Coastwise					
	Commodity	Total	Receipts	Shipment	<u>Through</u> Upbound				
Total, a	all commodities	3,949	576	3,346	27				
Total po	etroleum and petroleum products	2,818	518	2,828	19				
Sub 2100	ototal crude petroleum crude petroleum	75 75	72 72	4 4					
Subtota 2211 2330 2340 2450 2429	al petroleum products gasoline distillate fuel oil residual fuel oil lube oil & greases naphtha & solvents	2,743 1,654 322 144 570 27	446 21 83 59 256 27	2,278 1,633 239 85 314	19				
2430 2990	asphalt, tar & pitch petro. products nec	19 7		7	19				
Total cl	hemicals and related products	1,059	4	1,050	5				
Sub 3212 3219 3220	ptotal other chemicals and related products benzene & toluene other hydrocarbons alcohols	1,059 31 105 113	4 4 	1,050 26 105 113	5				

O arrange ditte		Coastwise			
Commodity	Total	Receipts	Shipment	<u>Through</u> Upbound	
3271 sulphur (liquid) 3274 sodium hydroxide	352 4		352	4	
3276 metallic salts 3297 chemical additives 3299 chem. products nec	12 436 7	0	10 436 7	1	
Total crude materials, inedible except fuels	56	53	2	1	
Subtotal soil, sand, gravel, rock and stone 4338 soil & fill dirt	3 3		1 1	1 1	
Subtotal iron ore and scrap 4420 iron & steel scrap	53 53	53 53			
Subtotal sulphur, clay and salt 4782 clay refrac. mat.	0 0		0 0		
Subtotal other non-metal. min. 4900 non-metal. min. nec	0 0		0 0		
Total primary manufactured goods	14	1	13		
Subtotal primary iron an steel products 5320 i&s primary forms	11 11		11 11		
Subtotal primary non-ferrous metal products 5421 copper 5480 fab. metal products	3 1 1	1 1	1 1		
Total all manufactured equipment, machinery and products	s 2	0	0	1	
7110 machinery (not elec) 7400 manufac. wood prod.	0	0	0	1	
Ton-miles (x1000) Coastwise	199,731	28,002	169,459	2,270	

		_							
		Internal							
Commodity	Total	Inbou	ınd	Outb	ound	Thro	ough	Ir	ntra
		Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd
Total, all Commodities	50,181	5,879	1,529	1,226	7,880	14,797	17,425	972	474
Total coal	107	1	1	48		5	51		
1100 Coallignite 1200 coalcoke	8 99	1	1	48		5	7 44		
Total Petroleum and Petroleum products	27,660	2,935	860	994	5,096	7,360	9,673	510	231
Subtotal crude petroleum	5,654	841		30	545	852	3,353	23	10
2100 crude petroleum	5,654	841		30	545	852	3,353	23	10

12.A-4 EIIP Volume III

						In	ternal			
Commod	ity	Total	Inbou	ınd	Outb		Thro	ugh	Ir	ntra
			Upbound I	Downbnd	Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd
Subtotal petroleum		22,006	2,094	860	964	4,551	6,508	6,320	487	222
products	•	5,294 290	581	45	162 130	778	1,526 92	2,010 67	86	106
2211 gasoline 2221 keroser 2330 distillate	ne	4,494	492	48	107	1,291	691	1,793	62	10
oil		5,613	483	58	290	1,657	1,863	1,057	198	7
2340 residua 2350 lube oil greases	&	1,112	23	4	137	219	519	207	2	1
2410 petro.je	elly&	56					51	5		
waxes 2429 naphtha solvent		2,119	384	37	4	369	571	538	126	90
2430 asphalt pitch	,tar&	1,075	11	3	1	22	767	271		
2540 petrolei coke	um	776	8	438	64		241	20		4
2640 liquid na gas	atural	552	58	181		55	124	131		4
2990 petro. product	snec	624	54	47	67	159	63	221	15	
Total chemic and related products	als	16,101	1,439	53	161	2,367	5,789	5,587	462	243
Subtotal		741	1	0		0	151	588		
fertilizers 3110 nitroger	nous	506					71	436		
fert. 3120 phosph	atic	135					6	129		
tert. 3130 potassi		4		0				3		
3190 fert.&m nec	iixes	96	1				75	20		
Subtotal oth chemicals and	i	15,360	1,437	53	161	2,366	5,638	5,000	462	243
related production 3211 acylic		1,084	386			5	134	559		
hydroca 3212 benzen	e&	1,369	196	32	7	485	99	362	33	156
toluene 3219 other hydroca		4,669	96	6	122	417	3,015	814	197	
3220 alcohol 3230 carboxy acids	S	2,559 381	119 27	2	1	564 57	589 252	908 45	33	43
3240 nitroger	n func.	813	102			280	374	57		
comp. 3260 organic nec	comp.	602	57			3	242	299		
3271 sulphur 3272 sulphur	ic acid						5	30		
3273 ammon		231 1,016				45	35	132		
3274 sodium hydroxi	de	970	30			186	250	800 540		
			40			29	352	549		

					Int	ternal			
Commodity	Total	Inbou	nd	Outbo			ugh	lr	ntra
		Upbound [Downbnd	Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd
3275 inorg. elem., oxides, & halogen salts	230	2-			1	99	129		
3276 metallic salts 3297 chemical additives	61 1,184		5 4	· ·	4 205	10 332	42 106	199	43
3298 wood & resin chem.	2					2			
3299 chem. products nec	407	29	4	21	86	98	169		
Total crude materials, inedible except fuels	3,003	1,136	98	1	15	1,239	515		
Subtotal forest products, wood and chips	13	0				3	9		
4110 rubber & gums	3					3			
4189 lumber 4190 forest products nec	2 8	0					2 8		
Subtotal soil, sand, gravel,	1,029	768	53		1	2	205		
rock and stone 4432 limestone 4323 gypsum 4327 phosphate	390 57 7	300	52 				38 57 7		
rock 4331 sand& gravel	496	458	0		1	2	35		
4335 waterway improve.mat	73	10	0				63		
4338 soil & fill dirt Subtotal iron	6 558				5	140	6 50		
ore and scrap 4410 iron ore	115					9	39		
4420 iron & steel scrap	443	295			5	131	12		
Subtotal	68		43				25		
4515 marine shells	68		43				25		
Subtotal non-ferrous ores and scrap	1,119	3				1,067	49		
4650 aluminum ore 4670 manganese	1,058 51	3				1,043 19	14 29		
ore 4690 non-ferrous ores nec	11					5	6		
Subtotal sulphur, clay and salt	16	2	0	0	4	3	7		
4782 clay & refrac. mat.	16	2	0	0	4	3	7		
Subtotal slag 4860 slag	108 108				3 3		105 105		

12.A-6

					In	ternal			
Commodity	Total	Inbou	nd	Outb	ound	Thro	ough	In	ıtra
-		Upbound [Downbnd	Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd
Subtotal other	91	0	2	1	2	23	63		
non-metal. min. 4900 non-metal min. nec	91	0	2	1	2	23	63		
Total primary manufactured goods	1,856	297	2	1	277	106	1,173		
Subtotal paper products	14		0				14		
5110 newsprint 5120 paper& paperboard	14 0		0				14 		
Subtotal lime, cement and glass	101	88	0	0	0	10	3		
5210 lime 5220 cement & concrete	3 98	88	0	0	0	10	3		
Subtotal primary iron and steel	1,638	209	0	0	272	69	1,088		
products 5312 pigiron 5315 ferro alloys 5320 i&s primary	281 81 68	206 1			 15	3 9 5	72 70 48		
forms 5330 i&s bars &	568					26	542		
sheets 5360 i&s bars & shapes	274				257	9	8		
5370 i&s pipe & tube	246	1	0	0		5	239		
5390 primary i&s nec	121					12	109		
Subtotal primary non-ferrous	97		1		4	27	64		
metal products 5421 copper	2					2			
5422 aluminum 5429 smelted prod.	8					2	1 6		
nec 5480 fab. metal products	86		1		4	24	56		
Subtotal primary wood	5			1	1		4		
products 5540 primary wood prod.	5			1	1		4		
Total food and farm products	736	16	5	15	61	247	392		
Subtotal grain 6241 wheat 6344 corn 6442 rice 6445 oats 6447 sorghum grains	347 116 7 200 11 13					92 48 7 24 13	255 68 		

		Internal							
Commodity	Total	Inbound		Outbound		Through		Intra	
		Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd
Subtotal oilseeds 6522 soybeans	16 16				11 11	5			
Subtotal vegetable	9					6	3		
products 6653 vegetable oils 6654 vegetables & prod.	3 6					6	3		
Subtotal processed grain	28		4	13	3	5	4		
and animal feed 6746 wheat flour 6838 animal feed, prep.	5 24		4	13	1	3 2	4		
Subtotal other agricultural	337	16	1	2	48	139	130		
products 6835 fish, prepared 6838 tallow,	3					3	8		
animal oils 6861 sugar 6865 molasses 6871 coffee	204 28 1					124 2 0	79 27 0		
6885 alcoholic beverages	11						11		
6887 groceriës 6888 water&ice 6889 food products nec	0 76 7		1	2	0 48 0		5		
Total all manufactured equipment, machinery and	172	26	2	3	59	51	32		
products 7110 machinery (not elec)	120	25	2	3	57	13	21		
7210 vehicles & parts	0				0				
7230 ships & boats 7300 ordnance & access.	0 5					0	0 5		
7500 textile products	6					3	3		
7600 rubber & plastic pr.	16					15	1		
7900 manufac. prod. nec	25				2	20	2		

12.A-8

Commodity		Internal								
	Total	Inbound		Outbound		Through		Intra		
		Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd	Upbound	Downbnd	
Total waste and scrap nec	547	29	509	3	5		1			
8900 Waste and scrap nec	I 547	29	509	3	5		1			
Ton-miles Internal (x100)	3,033,660	159,544	32,842	25,880	139,905	1,194,804	1,456,126	17,674	6,713	
Tons All Traffic (x (1000) Ton-miles All Traffic (x 1000))	103,254 3,356,592							